

Trade name: Permanent Marker Black Ink

Status: 08.03.2011

Version: 1.0.0 / GB

1.) Identification of the substance/mixture and of the company/undertaking

Trade name

Permanent Marker Black Ink

NN50-A / NN60-A / NX50-A / NX60-A / NXS15-A / NR2-A / NR3-A

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Ink for stationery products

Details of the supplier of the safety data sheet

Address

Pentel Bürobedarf-Handelsgesellschaft mbH
Lademannbogen 143
22339 Hamburg
GERMANY

Telephone no. +49 (0) 40 / 53 80 91 - 0

Fax no. +49 (0) 40 / 53 85 58 - 7

Information provided by / telephone

+49 (0) 40 / 53 80 91 - 0

Emergency telephone

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

Advice on Safety Data Sheet

sdb_info@umco.de

2.) Hazards identification

Classification of the substance or mixture

Classification in accordance with Directive 67/548/EEC or 1999/45/EC

F; R11

R43

R67

Xi; R38

Xi; R41


Label elements

Labelling according to Directive 1999/45/CE

Hazard symbols



Highly flammable



Irritant

Hazardous component(s) to be indicated on label, contains:

Colophonium

Benzenesulfonic acid, C10-16-alkyl derivs.

R phrases

11

Highly flammable.

38

Irritating to skin.

41

Risk of serious damage to eyes.

43

May cause sensitisation by skin contact.

67

Vapours may cause drowsiness and dizziness.

S phrases

2

Keep out of the reach of children.

24/25

Avoid contact with skin and eyes.

Trade name: Permanent Marker Black Ink

Status: 08.03.2011

Version: 1.0.0 / GB

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 37/39 Wear suitable gloves and eye/face protection.
 46 If swallowed, seek medical advice immediately and show this container or label.

Labelling information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

3.) Composition / information on ingredients**Hazardous ingredients****ethanol**

EC no.	200-578-6	Index no.	603-002-00-5	CAS no.	64-17-5
Concentration	> 30	< 50	%-b.w.		
Classification	F; R11				
Hazard symbols	F	R phrases	11		

n-propanol, propan-1-ol

EC no.	200-746-9	Index no.	603-003-00-0	CAS no.	71-23-8
Concentration	> 10	< 30	%-b.w.		
Classification	F; R11 Xi; R41	R67			
Hazard symbols	F; Xi	R phrases	11-41-67		

propan-2-ol

EC no.	200-661-7	Index no.	603-117-00-0	CAS no.	67-63-0
Concentration	> 5	< 10	%-b.w.		
Classification	F; R11 Xi; R36	R67			
Hazard symbols	F; Xi	R phrases	11-36-67		

Colophonium

EC no.	232-484-6	Index no.	650-015-00-7	CAS no.	8050-09-7
Concentration	> 5	< 10	%-b.w.		
Classification	R43				
Hazard symbols	Xi	R phrases	43		

benzyl-alcohol

EC no.	202-859-9	Index no.	603-057-00-5	CAS no.	100-51-6
Concentration	> 5	< 10	%-b.w.		
Classification	Xn; R20/22				
Hazard symbols	Xn	R phrases	20/22		

Benzenesulfonic acid, C10-16-alkyl derivs.

EC no.	271-528-9	Index no.	-	CAS no.	68584-22-5
Concentration	> 1	< 5	%-b.w.		
Classification	C; R35 Xn; R22				
Hazard symbols	C	R phrases	22-35		

sulphuric-acid

EC no.	231-639-5	Index no.	016-020-00-8	CAS no.	7664-93-9
Concentration	> 1	< 5	%-b.w.		
Classification	C; R35				
Hazard symbols	C	R phrases	35		

4.) First aid measures**General information**

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners !

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). Seek medical assistance.

After ingestion

Do not induce vomiting. Summon a doctor immediately. Never give anything by mouth to an unconscious person.

5.) Fire-fighting measures**Suitable extinguishing media**

Alcohol-resistant foam; extinguishing powder; Carbon dioxide; Water spray jet

Extinguishing media that must not be used for safety reasons

Full water jet

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)

Special protective equipment for fire-fighters

Use self-contained breathing apparatus. Wear protective clothing.

Other information

Cool endangered containers with water spray jet. Suppress gases/vapours/mists with water spray jet.

6.) Accidental release measures**Personal precautions**

Refer to protective measures listed in sections 7 and 8. Ensure adequate ventilation. Keep away sources of ignition. Do not inhale vapours. Avoid contact with skin, eyes and clothing.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Methods for cleaning up/taking up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

7.) Handling and storage**Handling****Advice on safe handling**

Provide good ventilation of working area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far as possible by the state of the art.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition.

Storage**Requirements for storage rooms and vessels**

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

Advice on storage assembly

None known

Further information on storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

8.) Exposure controls / personal protection**Exposure limit values****ethanol**

CAS no. 64-17-5
EC no. 200-578-6

List of approved workplace exposure limits (WELs) / EH40

Ethanol				
TWA	1920	mg/m ³	1000	ml/m ³

n-propanol, propan-1-ol

CAS no. 71-23-8
EC no. 200-746-9

Trade name: Permanent Marker Black Ink

Status: 08.03.2011

Version: 1.0.0 / GB

List of approved workplace exposure limits (WELs) / EH40

Propan-1-ol				
TWA	500	mg/m ³	200	ml/m ³
STEL	625	mg/m ³	250	ml/m ³
Skin resorption / sensibilisation	Sk			

propan-2-ol

CAS no.	67-63-0
EC no.	200-661-7

List of approved workplace exposure limits (WELs) / EH40

Propan-2-ol				
TWA	999	mg/m ³	400	ml/m ³
STEL	1250	mg/m ³	500	ml/m ³

sulphuric-acid

CAS no.	7664-93-9
EC no.	231-639-5

List of approved workplace exposure limits (WELs) / EH40

Sulphuric acid				
TWA	1	mg/m ³		

Exposure controls**Personal protective equipment****Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Eye protection

Safety glasses with side protection shield (EN 166)

Skin protection

Normal chemical work clothing.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

9.) Physical and chemical properties**General information**

Form	liquid
Colour	black
Odour	alkohol-like

Important health, safety and environmental information**Changes in physical state**

Type	Boiling point	
Value	78	°C

Flash point

Value	14,5	°C
-------	------	----

Density

Value	0,88		g/cm ³
Reference temperature	20	°C	

Trade name: Permanent Marker Black Ink

Status: 08.03.2011

Version: 1.0.0 / GB

Viscosity

Type	dynamic		
Value	4,2		mPa*s
Reference temperature	20	°C	
Type	kinematic		
Value	4,77		mm²/s
Reference temperature	20	°C	

10.) Stability and reactivity

Conditions to avoid

Protect from sun.

Materials to avoid

None known.

Hazardous decomposition products

No hazardous decomposition products known.

11.) Toxicological information

Experience in practice

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness.
Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin.
Irritating to eyes.

Other information

Product specific toxicological data are not known.

12.) Ecological information

Other information

Ecological data are not available. Do not discharge product unmonitored into the environment.

13.) Disposal considerations

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

14.) Transport information

Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	1263
Technical name	PAINT
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3

Transport IMDG

Class	3
Packing group	II
UN number	1263
Proper shipping name	PAINT
EmS	F-E+S-E
Label	3

Trade name: Permanent Marker Black Ink

Status: 08.03.2011

Version: 1.0.0 / GB

Transport ICAO/IATA

Class	3
Packing group	II
UN number	1263
Proper shipping name	Paint
Label	3

15.) Regulatory information**Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances**

Remarks Annex I, part 2, category 7 b

16.) Other information**Relevant R-phrases (chapter 3):**

R11	Highly flammable.
R20/22	Harmful by inhalation and if swallowed.
R22	Harmful if swallowed.
R35	Causes severe burns.
R36	Irritating to eyes.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.
R67	Vapours may cause drowsiness and dizziness.

Department issuing safety data sheet

UMCO Umwelt Consult GmbH

Georg-Wilhelm-Str. 183 b, 21107 Hamburg, Germany

Tel.: +49 40 / 41 92 13 00 Fax: +49 40 / 41 92 13 57 e-mail: umco@umco.de

This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.